

64 Channel NVR

Model - OP-64C-NVR



**HIGH DEFINITION
RESOLUTION**



**AUDIO AND ALARM
SUPPORT**



**RECORDING SPEED
FOR ALL CHANNELS**



**RACK
MOUNT**

High performance with maximum application

Technical Detailing

Features	Description
Type of Recording Device	NVR
Camera Support	IP Camera, PTZ Camera
Material of the Casing construction	Alluminium
Mounting bracket	Rack Mounted (4U)
Resolution	High Definition (1920 x 1080)
VIDEO Particulars	
Video Input	IP Based 64 Channels
Video Output	64 Channels
Compression	H.264, MJPEG, MPEG4
Resolution	Full HD 1920 x 1080
Frame Rate	25fps (recording speed for all channels)
Display Image	Real time per channel
Audio & Alarm	
Supported	
Audio & Alarm Input	64
Audio & Alarm Output	8
Compression	A-Law, G.726, G.711
Simultaneous two way audio support	1
Post Alarm Recording	20 second
Video Content Analytics	Motion Detection, Intrusion Detection, Tampering
Storage	
Internal Hard Drive Interface	SATA II
Number of Hard Disks	8 Hard Disk (4TB per hard disk)
Total Storage	32 TB expandable upto 32 TB
Networking Particular	
Supported Interface	Ethernet, HDMI, VGA, USB, RS 232
Ethernet	10/100/1000 Base TX
Protocols	Supports HTTP, UDP, DNS, DDNS, SNMP, IGMP, DHCP, RTP, RSTP, RTSP, TCP/IP, RTCP, NTP, UPnP, SMTp, FTP, ICMP, QoS
Simultaneous local views	4

Simultaneous Monitoring Connections	8
No of cameras viewed	64
Minimum Speed	512 Mbps
No of Ports	HDMI Ports x 2, USB Ports x 2, Ethernet Port x 2, VGA Port x 1, Serial Port x 1

Playback Management

Camera	Add, Edit, Delete, Use Master account, Use Specific account
Total Management	Group management, Group add, Delete
Page Preview	Video Window, Multi Monitor Support, Electronic Map on two separate monitors
Bookmarks	Forward, Backward, adjustable playback speed, Full Screen, Next Camera, Previous Camera, Repeat
Search	Date, Time, Event, Log, Motion, Bookmarks

Power Supply

Power Consumption	250 Watt
Power Input	230 ± 10%, 50Hz × 12 V DC × 24 V DC

Security

Encryption Type	HTTP (SSL/TSL)
Security	Multi-Level User ID / Password

Features

On Screen Display	Support
Recorder support recording	NAS Directly
Remote Administration	Configuration And Status Using Web Based Tool
System Update	Remote System Update
PC Client	PC Application Client With A Channel Recording Feature Support
Video Loop	Support

Add-on information

Standard 1 year warranty	
Operates on Relative Humidity Non-Condensing	90%
Operating Temperature Range	-10 to +50 degree Celsius

For queries- contact@oscarpro.com