Oscars**Pro**

HIGH QUALITY ACCESSORIES

"High quality accessories"

100-Watt wall mount Speaker- Pro-10MS

Speaker 2 Way drivers, mounting bracket

Effective Frequency Range 100 Hz – 17 kHz

Sensitivity 90 dB Impedance 8 Ohm

SPL 94dB (1W/1M)

Wireless LAN Card In- Built

Wi-Fi In- Built

Max. SPL 113dB (W/1M)

LF & HF Transducer 8-inch woofer & 2-inch tweeter

Power Consumption 100 watts

15-Meter USB Booster Cable Type A male to Female

Audio/Video 100 Mbps

Transmission speed

Connector Material Silver Plated

Type USB Type A Male to USB Type-A Female port

Cable Diameter 2.5 mm Length 15 M

Cable Material Plastic + Copper+ PVC

Conductor Material Copper

6-Port Audio Mixing Console

Phantom Power +48V

I/O Ports Stereo Bus x1, Mic x2 / Line Inputs x6 (mono x2 + stereo x2), XLR balanced

outputs

Channel 6-Channel Mixing Console

Sound effects High-grade effects: SPX with 6 programs

1x4 HDMI Switcher

HDMI Switcher 1x Input, 4x Output

Output Resolution 1080p

Output Status Led Indicator x4

Bandwidth 2.5 Gbps
HDMI & HDCP Supported

4x1 Full HD video Mixing Switcher

HDMI Switcher 4x Input, 1x Output

Output Resolution 1080p

Output Status Led Indicator x4

Video Layout 1,2,3,4 HDMI Input supported on single screen

Full HD Wireless Presentation System with USB Dongle

Wireless Frequency 2.4 Ghz.

Data Transfer Rate 1000 mbps

Frame Rate 30 fps

Maximum Number of 2 Number

Simultaneous sources on Screen & Connections

with the system

Output Resolution 1080p

Wireless Standards 802.11 a/b/g/n

Wireless Security WPA2-PSK/TKIP-AES

Wireless Range 15m

Medium of data Through dongle

transmission (From Computer/Laptop to

system)

Essential Accessories Available

Interfaces 1x HDMI, 1x USB, 1 x RJ45

HDMI Capture Card

Bandwidth 2.5 Gbps

I/O Ports Input: HDMI x1, Output: HDMI x1, USB x1

Output Resolution 1080p

USB Video Output USB Capture HDMI & HDCP Supported

HDMI to RJ45 KVM Transmitter

Receiver (Rx) I/O HDMI x1 (Output), HDBT x1 on RJ45 (Input)
Transmitter (Tx) HDMI x1 (Input), HDBT x1 on RJ45 (Output)

Transmission Range Up to 50 meters

Output Resolution 1080p
HDMI & HDCP Supported