

OscarsPro

VIDEO CONFERENCING CAMERA

"Give your surveillance a new high-definition quality with OscarsPro"



Model: Pro-TS-350

| 4K Camera- Pro-TS-350 | |
|--|---|
| <p>Camera</p> <p>2.07M effective Pixels, Progressive Scan Mode, 1/2.7inch CMOS Sensor, Lens focus arrangement f4.42mm~88.5mm, F1.8~F2.8 Aperture (Iris), 1080p at 60fps and 30fps Camera Resolution, 16 times digital and 20 times optical zoom, Point 5 Lux (F1.8 AGC) minimal illumination, Preset Accuracy, 1/30s~1/10000s shutter speed, 2D, 3D, Flip and Mirror Digital Noise Reduction, Support backlight compensation, ≥55dB Video S/N, 60.7 Degree 34.1 view angle, Plus and Minus 170 degree and minus 30 degree ~ Plus 90 Degree horizontal and vertical rotation range, 1.7 degree~100 degree per second Pan and 1.7 degree ~ 70 degree per second Tilt Range, 255 degree and 10 remote control presets with 0.1 degree accuracy; Auto, Indoor, Outdoor, One Push, Manual, Image Freeze; Video Resolution: 1080p/60, 1080p/50, 1080i/60, 1080i/50, 1080p/30, 1080p/25, 720p/60, 720p/50;</p> | <p>Interface and Function</p> <p>HIGH-DEFINITION OUTPUT THROUGH HDMI, RJ45, USB 3.0, CVBS; SD Output: CVBS: 3.5mm x 1; NETWORK INTERFACE:RJ45 10M/100M Ethernet Interface; AUDIO INTERFACE: 3.5 MM AUDIO JACK MIC IN/LINE IN; COMMUNICATION INTERFACE: RS232 IN & OUT, RS485, IP, Power Jack Jeita (DC In 12V); AAC Audio Encoding, Direct recording to USB Flash Disk, High SNR for CMOS Sensor for Low Light Conditions, Remotely controlled function with help of high speed communication, Handheld remote control</p> |
| <p>Network and USB Features</p> <p>Network: H.265/H.264/MJPEG, Main and Sub Stream; Main Stream (1920x1080, 1280x720, 1024x576) and Sub streams (1280 x 720, 720 x 576, 320x240), Video Bit Rate: 128kbps ~ 8192kbps; Frame Rate: 50hz: 1fps ~ 50fps, 60hz: 1fps ~60fps; Audio Bit Rate: AAC 96kbps, 128kbps, 256kbps; TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast Supported Protocols USB: YUV 4:2: 2 color system, 1080p at 60fps video format on USB 3.0, Audio on USB supported, Windows 10/8/7, Mac, Linus and Android OS Supported</p> | <p>Video System</p> <p>HDMI: 4K@30fps, 1080P@60fps, 1080P@50fps, 1080I@60fps, 1080I@50fp, 1080P@30fps, 1080P@25fps, 720P@60fps 3G-SDI: 1080P@60fps, 1080P@50fps, 1080I@60fps, 1080I@50fp, 1080P@30fps, 1080P@25fps,720P@60fps</p> |
| <p>Accessories</p> <p>All required cables and connector, User Manual, Power Adapter and IR Remote Control</p> | <p>Power and Operational</p> <p>Maximum 12W power consumption, DC 12 Volts Input Voltage, Maximum 1.0A current consumption, -10 to 40 degree operating and -40 to 60 degree Celsius storage temperature</p> |
| <p>Stand</p> <p>Optional stand provide with camera</p> | |